

# V-RAD SELECT



# Quick adjust torque with equal power in forward and reverse

ELECTRIC




V-RAD Select electric torque wrench is used for the installation or removal of heavy-duty fasteners where accuracy, power, and safety are required. Quick adjust torque settings. Equal power in forward and reverse.

## FEATURES

- Torque ranges up to 3,000 ft. lbs./ 4,000 Nm
- Digital torque settings to increase and decrease the value by 10 ft. lbs./ 10 Nm
- Available in both 120V or 230V

## CASE

Durable, light weight, shock proof.  
Designed to protect your RAD investment.



## IMPERIAL

| PART NUMBER | TOOL MODEL        | DRIVE SIZE | TORQUE (ft. lbs.)<br>LOW | TORQUE (ft. lbs.)<br>HIGH | RPM | WEIGHT (lbs.) | DIMENSION A | DIMENSION B | DIMENSION C | DIMENSION D |
|-------------|-------------------|------------|--------------------------|---------------------------|-----|---------------|-------------|-------------|-------------|-------------|
| 25628       | V-RAD SELECT 1000 | 0.75"      | 100                      | 1000                      | 8.8 | 8.6           | 12"         | 2.5"        | 2.9"        | 8"          |
| 25629       | V-RAD SELECT 1500 | 1.0"       | 150                      | 1500                      | 5.7 | 9.6           | 12.25"      | 2.7"        | 2.9"        | 8"          |
| 25631       | V-RAD SELECT 3000 | 1.0"       | 300                      | 3000                      | 2.7 | 13.7          | 13.5"       | 3.1"        | 3.1"        | 8"          |

## METRIC

| PART NUMBER | TOOL MODEL          | DRIVE SIZE | TORQUE (Nm)<br>LOW | TORQUE (Nm)<br>HIGH | RPM | WEIGHT (Kg) | DIMENSION A (mm) | DIMENSION B (mm) | DIMENSION C (mm) | DIMENSION D (mm) |
|-------------|---------------------|------------|--------------------|---------------------|-----|-------------|------------------|------------------|------------------|------------------|
| 25633       | V-RAD SELECT 1400-M | 0.75"      | 140                | 1400                | 8.8 | 3.9         | 305              | 64               | 74               | 203              |
| 25634       | V-RAD SELECT 2000-M | 1.0"       | 200                | 2000                | 5.7 | 5.9         | 311              | 69               | 74               | 203              |
| 25635       | V-RAD SELECT 3400-M | 1.0"       | 400                | 3400                | 2.7 | 6.2         | 343              | 79               | 79               | 203              |
| 25636       | V-RAD SELECT 4000-M | 1.0"       | 400                | 4000                | 2.7 | 6.2         | 343              | 79               | 79               | 203              |

Accuracy of +/-5%, Repeatability of +/-2%



## ADVANCED BOLTING SOLUTIONS PVT. LTD.

HO: "ABS House", Plot No. W-116 (A),  
T.T.C. Industrial Area, MIDC Khairane,  
Navi Mumbai - 400 710.

Tel: +91 22 3526 4444  
E-mail: marketing@absgroup.in  
Web: www.absgroup.in