

E-RAD BLU



90 DEGREE*



OFFSET*

*Only available on certain models.



SHOWN WITH OPTIONAL MOUNTING ACCESSORY



CASE

Durable, light weight, shock proof. Designed to protect your RAD investment.



Ability to use different handles with controller case

ELECTRONIC



E-RAD BLU precision torque wrench tools are designed to provide a high degree of accuracy (+/- 2.8%) and repeatability (+/- 2%). Using a patented gearbox design and the precision of an electric AC Servo motor, these tools deliver smooth continuous torque. Best of all, it's the most affordable system on the market.

FEATURES

- Advanced data logging and tool management features
- Military grade single cable and connector system
- Available in a 90-degree gearbox
- LED indicator lights (pass/fail)
- Push-button select torque
- Lightweight and ergonomic pistol grip


TOUCH CONTROL CASE

- Easy to use interface
- Pre-sets for torque and angle adjustments
- Quick error-free torque and angle adjustments
- Complete recalibrations
- Data logging with export to laptop



RAD SMART SOCKETS™

RAD SMART SOCKETS™ can connect to the E-RAD BLU tool via Bluetooth technology. This combination allows you to automatically calibrate your E-RAD BLU to any joint!



IMPERIAL

| PART NUMBER | TOOL MODEL | DRIVE SIZE | TORQUE (ft. lbs.) LOW HIGH | RPM 120V 230V | WEIGHT (lbs.) | DIMENSION A | DIMENSION B | DIMENSION C | DIMENSION D |
|-------------|-------------------------------|------------|-------------------------------|------------------|---------------|-------------|-------------|-------------|-------------|
| 21980 | E-RAD BLU 700 | 0.75" | 100 700 | 15 30 | 12 | 13.25" | 2.5" | 3.0" | 10.65" |
| 24161 | E-RAD BLU 1500 | 1.0" | 200 1500 | 8 16 | 13 | 13.28" | 2.7" | 3.0" | 10.65" |
| 21981 | E-RAD BLU 2500 COMP | 1.0" | 250 2500 | 4.9 10 | 18 | 14.8" | 3.0" | 3.0" | 10.65" |
| 24221 | E-RAD BLU 2500 COMP-90 Degree | 1.0" | 250 2500 | 6 12 | 18 | 9.65" | 3.0" | 3.1" | 11.83" |
| 21982 | E-RAD BLU 3000 | 1.0" | 500 3000 | 4.1 8.5 | 23.5 | 16.75" | 3.4" | 3.5" | 11.29" |
| 21983 | E-RAD BLU 6000 | 1.5" | 1000 6000 | 2.1 4.5 | 29 | 16.5" | 4.0" | 3.5" | 11.29" |
| 21984 | E-RAD BLU 7500 | 1.5" | 1500 7500 | 1.5 3 | 33 | 17.0" | 4.25" | 4.25" | 11.29" |
| 24234 | E-RAD BLU 11K* | 1.5" | 3000 11000 | 1.2 2.3 | 43 | 18.3" | 5.0" | 5.0" | 11.29" |

METRIC

| PART NUMBER | TOOL MODEL | DRIVE SIZE | TORQUE (Nm) LOW HIGH | RPM 120V 230V | WEIGHT (Kg) | DIMENSION A (mm) | DIMENSION B (mm) | DIMENSION C (mm) | DIMENSION D (mm) |
|-------------|----------------------------|------------|-------------------------|------------------|-------------|------------------|------------------|------------------|------------------|
| 21985 | E-RAD BLU 950-M | 0.75" | 135 950 | 15 30 | 5.5 | 340 | 65 | 78 | 275 |
| 24162 | E-RAD BLU 2000-M | 1.0" | 270 2000 | 8 16 | 5.9 | 337 | 69 | 78 | 275 |
| 21986 | E-RAD BLU 3400-M COMP | 1.0" | 340 3400 | 4.9 10 | 7.6 | 380 | 76 | 78 | 275 |
| 22434 | E-RAD BLU 3400-90-M Degree | 1.0" | 340 3400 | 6 12 | 8.3 | 210 | 76 | 78 | 300 |
| 21987 | E-RAD BLU 4000-M | 1.0" | 675 4000 | 4.1 8.5 | 11 | 430 | 86 | 88 | 287 |
| 21988 | E-RAD BLU 8000-M | 1.5" | 1350 8000 | 2.1 4.5 | 13.5 | 419 | 100 | 100 | 287 |
| 21989 | E-RAD BLU 10K-M | 1.5" | 2000 10000 | 1.5 3 | 15 | 432 | 105 | 105 | 287 |
| 24224 | E-RAD BLU 15K-M* | 1.5" | 4000 15000 | 1.2 2.3 | 20 | 465 | 127 | 127 | 287 |

Accuracy of +/-2.8%, Repeatability of +/-2% | *Also available in a 2.5" square drive.



ADVANCED BOLTING SOLUTIONS PVT. LTD.

HO: "ABS House", Plot No. W-116 (A),
T.T.C. Industrial Area, MIDC Khairane,
Navi Mumbai - 400 710.

Tel: +91 22 3526 4444
E-mail: sales@absgroup.in
Web: www.absgroup.in