

E-RAD BLU-S



CASE

Durable, light weight, shock proof. Designed to protect your RAD investment.



SOFT SLING



Great for horizontal or vertical applications and allows the tool to easily pivot between these two orientations.

Supreme Transducer Technology with High Accuracy

ELECTRONIC



The integrated transducer measures torque output in real time, ensuring the tool stops precisely where it needs to. This feedback loop allows the E-RAD BLU-S to operate accurately regardless of the joint condition and will even allow you to check a previously tightened bolt without applying too much torque.

FEATURES

- Built-in transducer
- Advanced data logging and tool management features
- Password protection on three user levels: basic, intermediate, and advanced
- Operator identification ensures traceability of each torque sequence performed
- Capable of torque and angle bolting sequence
- LED indicator lights (pass/fail)
- Extremely low noise level at only 75dB


TOUCH CONTROL CASE

- Easy to use interface
- Pre-sets for torque and angle adjustments
- Quick error-free torque and angle adjustments
- Complete recalibrations
- Data logging with export to laptop



RAD SMART SOCKETS™

RAD SMART SOCKETS™ can connect to the E-RAD BLU tool via Bluetooth technology. This combination allows you to automatically calibrate your E-RAD BLU to any joint!



IMPERIAL

PART NUMBER	TOOL MODEL	DRIVE SIZE	TORQUE (ft. lbs.) LOW HIGH	RPM 120V 230V	WEIGHT (lbs.)	DIMENSION A	DIMENSION B	DIMENSION C	DIMENSION D
30079	E-RAD BLU-S 700	0.75"	100 700	15 30	13	14.96"	2.84"	3.03"	10.65"
28836	E-RAD BLU-S 2500 COMP	1.0"	250 2500	5 10	19	16.21"	3.41"	3.03"	10.65"
31190	E-RAD BLU-S 3000	1.0"	500 3000	5 10	24.5	17.76"	3.73"	3.48"	11.29"
31191	E-RAD BLU-S 6000	1.5"	1000 6000	2.1 4.5	30	17.71"	4.35"	3.48"	11.29"
31192	E-RAD BLU-S 7500	1.5"	1500 8000	1.5 3	34	18.53"	4.48"	3.48"	11.29"
29314	E-RAD BLU-S 11K*	1.5"	3000 11000	1.5 2.3	44	19.81"	5.21"	3.48"	11.29"

METRIC

PART NUMBER	TOOL MODEL	DRIVE SIZE	TORQUE (Nm) LOW HIGH	RPM 120V 230V	WEIGHT (Kg)	DIMENSION A (mm)	DIMENSION B (mm)	DIMENSION C (mm)	DIMENSION D (mm)
26937	E-RAD BLU-S 950-M	0.75"	135 950	15 30	5.9	380	72	77	270.5
26938	E-RAD BLU 3400-S-M COMP	1.0"	340 3400	5 10	8.6	412	87	77	270.5
22759	E-RAD BLU-S 4000-M	1.0"	675 4000	5 10	11.1	451	95	88	287
25282	E-RAD BLU-S 8000-M	1.5"	1350 8100	2.1 4.5	13.6	450	110.5	88	287
26939	E-RAD BLU-S 10K-M	1.5"	2000 10000	1.5 3	15.4	471	114	88	287
29315	E-RAD BLU-S 15K-M*	1.5"	4050 15000	1.5 2.3	20	503	132	88	287

Accuracy of +/- 2.8%, Repeatability of +/- 2% | *Also available in a 2.5" square drive.



ADVANCED BOLTING SOLUTIONS PVT. LTD.

HO: "ABS House", Plot No. W-116 (A),
T.T.C. Industrial Area, MIDC Khairane,
Navi Mumbai - 400 710.

Tel: +91 22 3526 4444
E-mail: sales@absgroup.in
Web: www.absgroup.in