

B-RAD SELECT



DISPLAY

Torque ranges up to 5000 ft. lbs. / 7000 Nm

BATTERY




The B-RAD Select Series offers higher speed and longer battery life while incorporating a new torque display with buttons. The B-RAD Select allows the user to easily select the target torque. Patented Product.

FEATURES

- Digital torque settings, able to increase or decrease the value by 10 ft. lbs./ 10 Nm
- Torque ranges up to 5,000 ft. lbs./ 7,000 Nm
- Equipped with the latest lithium-ion technology
- Suitable for pre-torque and service jobs where electricity or compressed air are not available
- Longer battery life

CASE

Durable, light weight, shock proof. Designed to protect your RAD investment.



IMPERIAL

PART NUMBER	TOOL MODEL	DRIVE SIZE	TORQUE (ft. lbs.) LOW	TORQUE (ft. lbs.) HIGH	RPM	WEIGHT (lbs.)	DIMENSION A	DIMENSION B	DIMENSION C	DIMENSION D
28283	B-RAD SELECT 500	0.75"	130	500	21.5	7.7	9.1"	2.5"	2.65"	10.3"
28285	B-RAD SELECT 1000	0.75"	200	1000	10.5	7.8	9.1"	2.5"	2.65"	10.3"
28286	B-RAD SELECT 1000-2	0.75"	400	1000	17	9.4	11"	2.5"	2.65"	10.3"
28287	B-RAD SELECT 1500	1.0"	300	1500	6	8.9	9.6"	2.7"	2.7"	10.3"
28288	B-RAD SELECT 1500-2	1.0"	300	1500	19.5	10.7	11.75"	2.7"	2.7"	10.3"
28289	B-RAD SELECT 3000	1.0"	600	3000	3	13.3	11.2"	3.2"	3.2"	10.5"
28290	B-RAD SELECT 3000-2	1.0"	600	3000	20	14.7	13.25"	3.2"	3.2"	10.5"
28291	B-RAD SELECT 5000	1.5"	1000	5000	2.1	19.3	11.6"	3.75"	3.75"	10.7"

METRIC

PART NUMBER	TOOL MODEL	DRIVE SIZE	TORQUE (Nm) LOW	TORQUE (Nm) HIGH	RPM	WEIGHT (Kg)	DIMENSION A (mm)	DIMENSION B (mm)	DIMENSION C (mm)	DIMENSION D (mm)
29594	B-RAD SELECT 275-M	0.75"	50	270	46.5	3.3	228	63	68	262
28264	B-RAD SELECT 700-M	0.75"	170	700	21.5	3.5	231	63	67	262
28266	B-RAD SELECT 1400-M	0.75"	270	1400	10.5	3.5	231	63	67	262
28267	B-RAD SELECT 1400-2-M	0.75"	540	1400	17	4.3	279	63	67	262
28268	B-RAD SELECT 2000-M	1.0"	400	2000	6	4.0	244	69	69	262
28269	B-RAD SELECT 2000-2-M	1.0"	400	2000	19.5	4.9	298	69	69	262
28270	B-RAD SELECT 4000-M	1.0"	800	4000	3	6.0	285	81	81	266
28271	B-RAD SELECT 4000-2-M	1.0"	800	4000	20	6.7	337	81	81	266
28272	B-RAD SELECT 7000-M	1.5"	1350	7000	2.1	8.8	295	95	95	272

Accuracy of +/-5%, Repeatability of +/-2%



ADVANCED BOLTING SOLUTIONS PVT. LTD.

HO: "ABS House", Plot No. W-116 (A),
T.T.C. Industrial Area, MIDC Khairane,
Navi Mumbai - 400 710.

Tel: +91 22 3526 4444
E-mail: marketing@absgroup.in
Web: www.absgroup.in